WHAT IS CLAIMED IS:

1. A method of preparing a sequence of signal samples for transmission, comprising the step of:
   for each occurrence of two consecutive equivalent samples, replacing the second-occurring equivalent sample with synchronization information.

2. A method of transmitting an incoming sequence of signal samples, comprising the steps of:
   for each of said incoming samples,
   (i) transmitting said sample if said sample is not equivalent to an immediately preceding sample, or
   (ii) transmitting a synchronization pattern if said sample is equivalent to the immediately preceding sample.

3. A method of transmitting an input stream of signal samples with synchronization information, comprising the steps of:
   sequentially monitoring said samples to detect a match condition characterized by the equivalence of two consecutive samples;
   if a match condition is detected, substituting the second-occurring equivalent sample with a synchronization pattern.

4. The method as recited in claim 3 wherein said substitution step occurs in real time.

PATENT

5. A system for transmitting a sequence of signal samples received from an input bus, comprising:

storage means coupled to said input bus for temporarily storing samples;

sample comparison means coupled to said storage means for comparing each sample with the immediately preceding sample, and generating a match signal when said sample is equivalent to the preceding sample;

output means coupled to said storage means and said comparison means for transmitting each sample in the absence of a match signal, and transmitting a synchronization pattern in the presence of a match signal.

6. A method of transmitting an incoming sequence of signal samples and receiving the transmitted samples, comprising the steps of:

for each of said incoming samples,

(i) transmitting said sample if said sample is not equivalent to an immediately preceding sample, or

(ii) transmitting a synchronization pattern if said sample is equivalent to the immediately preceding sample;

monitoring said transmissions at a receiving end to detect the occurrence of said synchronization pattern; and

outputting a received sample when a synchronization pattern is not detected, and outputting the immediately previous received sample when a synchronization pattern is detected.

90-3-816   -12-

7. A system for transmitting an incoming sequence of
signal samples and receiving the transmitted samples,
comprising:

  transmit means for monitoring said sequence of signal
    samples, transmitting a sample if said sample is
    not equivalent to an immediately preceding sample,
    and transmitting a synchronization pattern if said
    sample is equivalent to the immediately preceding
    sample;
  receive means, coupled to receive said transmission,
    for outputting a received sample when a
    synchronization pattern is not detected, and
    outputting the immediately previous received
    sample when a synchronization pattern is detected.

A 2